

## Cable Tie Tag

Transponder ON METAL  
Special Form

### PART ID: 2022-XX-XXX-XX

The RFID CABLE TIE TAG 27x20 mm is available as LF, HF, NFC or UHF version and is used to identify devices, machines and equipment by easy mounting method. The RFID CABLE TIE TAG LF, HF, NFC, UHF can be used for On-Metal and Non-Metal applications



### Main Specifications

Frequencies	LF HF UHF
Material	Polyamid
Operating Temperature	-40°C to 85°C
IP Class	IP68
Compliance	RoHs & Reach
Key Features	ON-Metal Use, Rough Environment, Durable Housing, High Durability
Options	Laser Engraving, Logo, Color, Other Chips On Request

### Full Specifications

Product ID	2022
Name	Cable Tie Tag
On Metal Use	yes
PEAK Performance	yes
Material	Polyamid
Shape	Ultrasonic Welded
Long Description	The RFID CABLE TIE TAG 27x20 mm is available as LF, HF, NFC or UHF version and is used to identify devices, machines and equipment by easy mounting method. The RFID CABLE TIE TAG LF, HF, NFC, UHF can be used for On-Metal and Non-Metal applications
Key Features	ON-Metal Use, Rough Environment, Durable Housing, High Durability
Options	Laser Engraving, Logo, Color, Other Chips On Request
Main Use	Asset Tracking

Article Type	Special Form
Length [mm]	27
Width [mm]	20.4
Hole	yes
Operating Temp °C (min)	-40
Operating Temp °C (max)	85
Storage Temp °C (min)	-40
Storage Temp °C (max)	85
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Cable tie
Compliance	RoHs & Reach

#### VARIANTS AND ICS

Color	Yellow Blue Green Black
LF	EM4200/Unique
HF	ICODE SLIX 2
UHF	Higgs 3

